DP 300 series

Precision hand-held calibrator



DP 300 series

The DP 300 series impresses with its rugged and reliable design. The choice of versions meets all requirements for industrial, service and laboratory applications.



Reliable regulation with precision and control

Technical specifications

Series-types

DP 300A

Accuracy Measuring range

Measuring medium

DP 300L

Accuracy Measuring range Measuring media Overload protection

DP 300C

Accuracy Measuring range Measuring media

DP 300P

Accuracy Measuring range Measuring media

DP 300H

Accuracy Measuring range Measuring media

Pressure connection

Supply Display

Interfaces

Dimensions Weight

Scope of delivery

0,01% FS

O...1,3 bar up to O...50 bar, absolute pressure Air

0,1% FS up to 0,08% FS 0...1 mbar, up to 0...20 mbar Non-corrosive gases 1 bar

0,025% FS

0...100 mbar up to 0...20 bar Gases and liquids (also corrosive)

0.05% FS

0...50 mbar up to 0...25 bar Non-corrosive gases and liquids

0.04% FS

0...20 bar up to 0...2000 bar Gases and liquids (also corrosive)

Compression fitting for 6/4 mm hose, high-pressure measuring connection for

measuring ranges > 15 bar or according

to customer requirement

8 x NiMH batteries HR6 (AA) incl. charger

2-line, 16 digits 10 mm high, different pressure units

USB or RS232

38 x 220 x 120 mm (H x W x D)

Approx. 1.250 g

Calibrator with case, mains charger, measuring hose, factory certificate,

PC software for

capturing, transmitting and storage

of readings on the PC



Neuglücker Weg 2 | 45529 Hattingen Tel. +49 (0) 2324 9430 50 Fax +49 (0) 2324 9430 55 info@mecotec.eu | www.mecotec.eu